

Specifications for Standard Models - variations available upon request

Model	Min Patch Size ¹ in. (cm)	Drill Depth ² in. (cm)	Hole Dia. in. (mm)	Drill Dist. From Corner in. (cm)	Air Req. cfm (m3)	Hose Size - (ID) ³ in. (mm)	Drill Motor	Chuck Size in. (mm)	Weight lb. (kg)
65B	24 & 30 (60.9 & 76.2)	8 & 12 (20.3 & 30.5)	1/2 - 7/8 (12.7 - 22.2)	6 (15.2)	20 (0.56)	3/4" (19.1)	CP 9C	3/4 RD X 3-3/4 (19.0 X 95.2)	65 (29.5)
65B	30 (76.2)	9 (22.9)	5/8 - 2 (15.9 - 50.8)	6 (15.2)	32 (0.90)	3/4" (19.1)	CP 14	7/8 X 3 1/4 (22.2 X 82.6)	85 (38.6)
110B	36 (91.4)	12 (30.5)	5/8 - 2 (15.9 - 50.8)	6 (15.2)	50 (1.40)	3/4" (19.1)	CP 22	7/8 X 3 1/4 (22.2 X 82.6)	170 (77.2)
210B	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	100 (2.80)	3/4" (19.1)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	230 (104.4)
210B-2*	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	200 (5.60)	1 1/4" (31.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	710 (322.3)
210B SRA	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	100 (2.80)	3/4" (19.1)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	385 (174.8)
210B-2 SRA	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	200 (5.60)	1 1/4" (31.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	1040 (404.1)
210-3 SRA	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	300 (8.40)	1 1/2 - 2" (38.1 - 50.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	2000 (908.0)
210-4 SRA	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	400 (11.20)	2" (50.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	2200 (988.8)
210-5 SRA	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	500 (14.00)	2" (50.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	2400 (1089.6)
210-3 EQ MT	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	300 (8.40)	1 1/2 - 2" (38.1 - 50.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	1400 (635.6)
210-4 EQ MT	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	400 (11.20)	2" (50.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	1700 (771.8)
210-5 EQ MT	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	500 (14.00)	2" (50.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	1900 (862.6)
210-6 EQ MT	48 (121.9)	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	6 (15.2)	600 (17.00)	2" (50.8)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	2100 (953.4)
20 UTL	N/A	18 (45.7)	5/8 - 2 1/2 (15.9 - 63.5)	N/A	100 (2.80)	3/4" (19.1)	CP 32A	7/8 X 3 1/4 (22.2 X 82.6)	207 (94.0)
210 TWIN VERTICAL	N/A	17 (43.2)	3/4 - 2 1/2 (19.0 - 63.5)	N/A	260 (7.28)	1 1/4" (31.8)	CP 69	1 X 4-1/4 (25.4 X 107.9)	930 (422.2)

1. Minimum patch size is the smallest area the unit will fit in and drill the depth listed

2. Drill depths given are standard - other drill depths available upon request

3. All sizes shown are for 25' of hose or less

* Back wheels must be configured in order to fit in a 48" area